

## Dräger Pac<sup>®</sup> 5500

Ideally suited for personal monitoring applications, the Dräger Pac 5500 provides quick detection of carbon monoxide, hydrogen sulfide or oxygen. Accurate, reliable and easy to use, this small, ergonomic instrument has no lifetime limitation.



### SMALL YET ROBUST

Small in size and light in weight, the Dräger Pac 5500 has been developed with the needs of industrial users and applications in mind. Providing easy, single-handed operation, even when wearing gloves, it is designed to withstand the toughest environments. The impact-resistant rubber housing is impervious to corrosive chemicals and meets the requirements of IP65 to ensure operation even when projected with water.

### SAFETY FIRST

The instrument's sensor has been specially positioned to allow gas access at both the top and front so that gas detection is continuous if the unit is placed in a pocket or if a gas inlet is accidentally covered.

### NO LIFETIME LIMITATION

Designed for long-term operation, the Dräger Pac 5500 boasts an unlimited lifetime. The battery and the sensor can be easily replaced on-site and without any additional equipment. Also, the dust and water filter on the front of the instrument can be replaced when clogged with dirt or mud.

### MINIATURE SENSOR TECHNOLOGY

Incorporating the latest miniature Dräger

XXS sensor technology, the Dräger Pac 5500 has been specifically developed for use in personal monitoring and handheld applications. Offering a long, expected lifespan from 5 to 8 years, these innovative sensors combine high performance with a fast reaction time of just ten seconds.

### CLEAR, HIGHLY VISIBLE DISPLAY

Clear and easy to see, the large liquid crystal display shows both the gas concentration and the measurement unit. As an option, the instrument can also be configured to display just the type of gas. The concentration is then displayed only when the set alarm levels have been exceeded. Language-free to avoid any misunderstanding, this continuous numeric display can also be back-lit to improve readability in darker environments.

In addition, labels in yellow (hydrogen sulfide) and blue (oxygen) are available to ensure that the instrument can be identified quickly even over a long distance.

### WARNINGS AND ALARMS

In addition to vibrating and audible, multi-tone alarms, the Dräger Pac 5500 issues a clear, 360° visual alarm via bright, flashing LEDs at the top and base



**Dräger Pac 5500**  
Reliable measurement results combined with no lifetime limitation.

of the instrument. Alarm thresholds can be set by the user, and gas alarms include both a pre and main alarm.

Bringing maximum confidence to the user, the instrument will also emit both pre and main alarms before loss of battery power. Should there be a problem with the electronics, the battery or the sensor, the user will receive a clear, immediate fault alarm and display indication. A further "life signal" option, which can be activated and/or disabled to suit specific requirements, is also available.

Bump tests usually take between 8 and 15 seconds and to ensure that they can be performed quickly and easily, the Dräger Pac 5500 can be used with the Dräger Bump Test Station. This economical unit allows both the instrument and sensor performance to be checked anywhere, without the need for additional power. Each successful test is automatically stored in the data logger whilst unsuccessful tests render the instrument "out of order". An optional mobile printer is also available for those applications where hard copies are required.

D-557-2009

#### DrägerSensors®

Dräger XXS Sensors provide longer operating times.

#### Large display

Clearly structured, language-free display shows all necessary information at one glance.

#### Robust housing

Impact-resistance combined with an ergonomic design.

#### High visibility

Colored labels are available to distinguish the instrument at a distance.



### BUMP TEST AND CALIBRATION

Most national regulations require users to test equipment against a known gas concentration on a regular basis. Bump tests check that instruments are functioning correctly. Equipped with adjustable bump test and calibration intervals to meet the needs of different applications, the Dräger Pac 5500 displays a warning as soon as a bump test or calibration is required. Should the warning be ignored, the instrument will automatically display an "out of order" error message. As an option, users can also select this same error message to indicate that the calibration interval has expired.

Fresh air calibration is requested within the boot sequence at start up and is easy to perform. Calibration can be carried out in the workshop by docking the instrument to a PC, and an optional automated test and calibration system is also available. The recommended inspection interval for Dräger Pac 5500 is 2 years.

### DATA LOGGER

Able to store up to 60 events complete with dates and times, the Dräger Pac 5500 incorporates an IR interface and can be easily linked to a PC via a connecting cradle. As a result, significant events such as switch on/off, gas and battery alarms,

error modes, configuration changes, fresh air calibrations and bump tests can also be downloaded, printed and stored.

**DRÄGER PAC® 5500 – AT A GLANCE**

- High performance Dräger XXS Sensors
- No lifetime limitation with simple battery, sensor and filter replacement
- 8-15 second function test with the Dräger Bump Test Station
- Optional calibration function after a failed function test
- Adjustable bump test interval
- Gas inflow from above and the front
- Optional high visibility labels for instrument recognition at a distance

**ORDER INFORMATION**

Description	Measuring Range	Default Alarm Threshold A1/A2	Resolution	Response Time	Order Code
Dräger Pac 5500 CO <sup>1)</sup>	0 – 500 ppm	30/60 ppm	1 ppm	15 sec.	83 22 008
Dräger Pac 5500 CO	0 – 500 ppm	by request	1 ppm	15 sec.	83 22 009
Dräger Pac 5500 H <sub>2</sub> S <sup>1)</sup>	0 – 100 ppm	10/20 ppm	0.1 ppm	15 sec.	83 22 010
Dräger Pac 5500 H <sub>2</sub> S	0 – 100 ppm	by request	0.1 ppm	15 sec.	83 22 011
Dräger Pac 5500 O <sub>2</sub> <sup>1)</sup>	0 – 25 Vol.-%	19/23 Vol.-%	0.1 Vol.-%	10 sec.	83 22 012
Dräger Pac 5500 O <sub>2</sub>	0 – 25 Vol.-%	by request	0.1 Vol.-%	10 sec.	83 22 013
Leather carrying case					45 43 822
Highly visible yellow label for H <sub>2</sub> S instruments					83 20 997
Highly visible blue label for O <sub>2</sub> instruments					83 20 996
<b>Communication Accessories</b>					
Dräger CC-Vision					64 08 515
Communication Module, complete with USB cable and Dräger Pac Vision software					83 18 587
<b>Calibration Accessories</b>					
Calibration adapter					83 18 588
Dräger Pac Module for Dräger E-Cal calibration system					83 18 589
Dräger Bump Test Station for Dräger Pac 5500, not including gas cylinder					83 17 410
Dräger Bump Test Station for Dräger Pac 5500 Complete with one test gas cylinder 58L (gas and concentration variable)					83 18 586
Dräger Bump Test Station for Dräger Pac 5500 The station for use with Dräger Mobile Printer, not including gas cylinder					83 19 559
Dräger Bump Test Station for Dräger Pac 5500 The station for use with Dräger Mobile Printer, complete with one test gas cylinder 58L (gas and concentration variable)					83 21 008
Printer Set for Dräger Bump Test Station Consisting of: Dräger Mobile Printer, single charger, rechargeable NiMH batteries, USB connection cable, positioning aid, Dräger CC-Vision					83 21 010
<b>Replacement Parts</b>					
Lithium battery					45 43 808
Water and dust filter					45 43 836

1) Default configuration Europe



ST-5827-2004

**Dräger Pac 5500**  
Single gas detector with no lifetime limitation.



ST-5604-2005

**Dräger Pac 5500**  
Dräger Bump Test Station for a quick and reliable function test.



ST-10148-2009

**Dräger Pac 5500**  
Dräger Pac 5500 with highly visible colored labels.

**TECHNICAL DATA**

Dimensions (W x H x D)	84 x 64 x 25 mm; 3.3 x 2.5 x 1.0 in.
Weight	120 g; 3.8 oz.
Ambient conditions	Temperature -30 – 50 °C; -20 – 120 °F Pressure 700 – 1300 hPa Humidity 10 – 90 % r. h.
Ingress protection	IP65
Display	Language-free LCD display, continuous indication of concentration, notice and alarm functions
Battery life (typical at 25° C)	8 hours of use per day, 1 minute alarm per day: CO, H <sub>2</sub> S: > 2 years O <sub>2</sub> : > 12 month
Alarms	Visual (360° flashing LEDs at top and bottom), audible (multi-tone >90 dB at 30cm;1ft), vibrating
Instrument life	No lifetime limitation
Guaranty	2 years
Event logger	Storage of up to 60 events including concentration levels, date and time
Approvals	CE-Sign (89/336/EEC, 94/9/EC) ATEX I/II M 1/1 G EEx ia I/IIC T4 UL Class I, II Div 1, Group A, B, C, D, E, F, G, Temp. Code T4 cUL Class I, II Div 1, Group A, B, C, D, E, F, G, Temp. Code T4 IECEX Ex ia II C T4 GOST 51330.0-99 (_60079-0-98); 51330.10-99 (_60079-11-99); _Exial / 0ExialICT4

**HEADQUARTERS:**  
Dräger Safety AG & Co. KGaA  
Revalstrasse 1  
23560 Lübeck, Germany

[www.draeger.com](http://www.draeger.com)

**SUBSIDIARIES:**

**AUSTRALIA**  
Dräger Safety Pacific Pty. Ltd.  
Axxess Corporate Park  
Unit 99, 45 Gilby Road  
Mt. Waverley. Vic 3149  
Tel +61 3 92 65 50 00  
Fax +61 3 92 65 50 95

**CANADA**  
Dräger Canada Ltd.  
7555 Danbro Crescent  
Mississauga,  
Ontario L5N 6P9  
Tel +1 905 821 89 88  
Fax +1 905 821 25 65

**P. R. CHINA**  
Beijing Fortune Draeger  
Safety Equipment Co., Ltd.  
Yu An Lu A 22, B Area  
Beijing Tianzhu Airport  
Industrial Zone  
Houshayu Shunyi District  
Beijing 101300  
Tel +86 10 80 49 80 00  
Fax +86 10 80 49 80-05

**FRANCE**  
Dräger Safety France SAS  
3c route de la Fédération,  
BP 80141  
67025 Strasbourg Cedex 5  
Tel +33 3 88 40 59 29  
Fax +33 3 88 40 76 67

**USA**  
Dräger Safety, Inc.  
101 Technology Drive  
Pittsburgh, PA 15275  
Tel +1 412 787 83 83  
Fax +1 412 787 22 07

**MEXICO**  
Dräger Safety S.A. de C.V.  
Av. Peñuelas No. 5  
Bodega No. 37  
Fraccionamiento Industrial  
San Pedrito  
Querétaro, Qro México  
Tel +52 442 246-1113  
Fax +52 442 246-1114

**NETHERLANDS**  
Dräger Safety Nederland B.V.  
Edisonstraat 53  
2700 AH Zoetermeer  
Tel +31 79 344 46 66  
Fax +31 79 344 47 90

**REP. OF SOUTH AFRICA**  
Dräger South Africa (Pty) Ltd.  
P.O.Box 68601  
Bryanston 2021  
Tel +27 11 465 99 59  
Fax +27 11 465 69 53

**SINGAPORE**  
Dräger Safety Asia Pte. Ltd.  
67 Ayer Rajah Crescent # 06 03  
139950 Singapore  
Tel +65 68 72 92 88  
Fax +65 67 73 20 33

**SPAIN**  
Dräger Safety Hispania S.A.  
Calle Xaudaró 5  
28034 Madrid  
Tel +34 91 728 34 00  
Fax +34 91 729 48 99

**UNITED KINGDOM**  
Dräger Safety UK Ltd.  
Blyth Riverside Business Park  
Blyth, Northumberland  
NE24 4RG  
Tel +44 1670 352 891  
Fax +44 1670 356 266