

Dräger Flame 5000

The Dräger Flame 5000 is an explosion proof colour imaging based flame detector. Each detector operates standalone and incorporates, within a single unit, an integrated CCTV system; digital signal processing and software algorithms to process live video image and interpret the characteristics of a flame.



SIMPLE INSTALLATION & COMMISSIONING

Installation is simple! The detector is easily installed with a stainless steel mounting bracket; this can be rotated to ensure optimum positioning of the detector in relation to the potential fire source.

Detector Flexibility

The detector can be operated as a standalone unit providing live video images, it can also be integrated with a control system or fire panel to provide fault, and fire signalling. This is achieved using a 0 to 20 mA, or relay outputs. An In-built memory card allows the detector to record before and after every alarm.

Advance Optical Verification

The optical verification facility is designed to check the window for contamination and to ensure the detectors field of view is not compromised by an obstruction placed immediately in front of the detector. The surveillance aspect of the detector eliminates the need to dispatch operators to investigate alarms. This reduces the risk of injury and also improves response time.

Easily Visible Status LED

A tri-colour LED which is visible at the front of the detector provides a simple status indication to personnel in close proximity to the detector. Green indicates normal operation; yellow indicates a fault and red indicates the presence of radiation.

Field of View

The Dräger Flame 5000 can detect fires of 0.1 m² or greater, at 44 m within a 90° Horizontal Field of View. The detector's Field of View is a rectangular pyramid shape and represents a radial projection of the sensing element, therefore giving it the greatest coverage area of any flame detector currently available.

False Alarm Immunity

The Dräger Flame 5000's advanced image processing algorithms are so discriminating that false alarms are all but non-existent.

Worldwide Approvals

The Dräger Flame 5000 has the option of being Aluminium, or Stainless Steel. It can be used worldwide with the following approvals: ATEX, IECEx, FM and CFM.



Dräger Flame 5000
Explosion proof colour imaging based flame detector

TECHNICAL DATA

Dräger Flame 5000

Type		Colour imaging based visual flame detector
Field of View		Horizontal 90°
Sensitivity		0.1 m ² gasoline fire at 44 m, (1 sq. ft fire at 144 ft)
Response Time		4 seconds, typical; configurable up to 30 seconds
Signal Output	Analogue	0 to 20 mA
	or 2 Relays for Fault & Alarm	Ratings 125 VAC, 0.5 A; 30 VDC, 2A (optional)
	Standard RS 485	
Supply Voltage		18 to 30 VDC, current consumption 6 watts (typical)
Ambient Conditions	Temperature	- 60 °C to + 85 °C, - 76 °F to + 185 °F
	Pressure	915 to 1055 hPa, 27.9 to 31.2 inch of Hg
	Humidity	0 to 99 %RH, non-condensing
Enclosure		IP 66, NEMA 4X
Cable Entry		M20, M25 or ¾" NPT
Dimensions (L x D, approx)		200 x 100 mm, 7.9 x 3.9 inches
Weight (approx)		2.5 kg, 5.5 lbs (2.8 kg, 6.2 lbs stainless steel)
Approvals	ATEX	II 2 G EEx d IIC T4
	IECEx	Ex d IIC T4
	FM/CFM	Class I, Division 1 Groups B, C and D Class I, Zone 1, AEx d IIC; T5

ORDER INFORMATION

Dräger Flame 5000	Order No
Dräger FS-5000	420 93 07
Dräger CCTV Balanced Line to BNC Video Converter	420 93 27
Dräger Flame 5000, M20, 4-20mA, PAL video mode, Aluminium	420 93 08
Dräger Flame 5000, M20, Relay, NTSC video mode, Aluminium	420 93 09
Dräger Flame 5000, ¾ NPT, Relay, NTSC video mode, Aluminium	420 93 10
Dräger Flame 5000, ¾ NPT, 4-20mA, PAL video mode, Aluminium	420 93 11
Dräger Flame 5000, M25, 4-20mA, PAL video mode, Aluminium	420 93 33
Dräger Flame 5000, M25, Relay, NTSC video mode, Aluminium	420 93 34
Dräger Flame 5000, M20, 4-20mA, PAL video mode, Stainless Steel	420 93 20
Dräger Flame 5000, M20, Relay, NTSC video mode, Stainless Steel	420 93 21
Dräger Flame 5000, ¾ NPT, Relay, NTSC video mode, Stainless Steel	420 93 22
Dräger Flame 5000, ¾ NPT, 4-20mA, PAL video mode, Stainless Steel	420 93 23
Dräger Flame 5000, M25, 4-20mA, PAL video mode, Stainless Steel	420 93 35
Dräger Flame 5000, M25, Relay, NTSC video mode, Stainless Steel	420 93 36

Dräger Safety AG & Co. KGaA
Revalstrasse 1
23560 Lübeck, Germany
Tel +49 451 882-2794
Fax +49 451 882-4991
www.draeger.com

SYSTEM CENTERS

P. R. CHINA
Beijing Fortune Draeger
Safety Equipment Co., Ltd.
Yu An Lu A 22, B Area
Beijing Tianzhu Airport
Industrial Zone
Houshayu Shunyi District
Beijing 101300
Tel +86 10 80 49 80 00
Fax +86 10 80 49 80 05

FRANCE

Dräger Safety France S.A.S.
3c, Route de la Fédération
67025 Strasbourg Cedex
Tel +33 388 40 76 76
Fax +33 388 40 76 67

SINGAPORE

Draeger Safety Asia Pte. Ltd.
67, Ayer Rajah Crescent # 06 03
139950 Singapore
Tel +65 68 72 92 88
Fax +65 67 73 20 33

UNITED KINGDOM

Draeger Safety UK Ltd.
Blyth Riverside Business Park
Blyth, Northumberland NE24 4RG
Tel +44 1670 352 891
Fax +44 1670 544 475

USA

Draeger Safety, Inc.
505 Julie Rivers, Suite 150
Sugar Land, TX 77478
Tel +1 281 498 1082
Fax +1 281 498 5190