

## Dräger Polytron® 8100 EC Detection of toxic gases and vapors

The Polytron® 8100 EC is Dräger's top of the line explosion proof transmitter for the detection of toxic gases or oxygen. It uses a high performance plug and play electrochemical DrägerSensor® to detect a specific gas. Besides a 3 wire 4 to 20 mA analog output with relays, it also offers Modbus and Fieldbus protocol making it compatible with most control systems.



## Benefits

---

### Durable, intelligent and sensitive – the DrägerSensor®

With unique electrochemical DrägerSensors, Polytron 8100 can detect over 100 toxic gases and oxygen. These long life sensors provide continuous detection even under the harshest conditions. DrägerSensors offer the industry's widest temperature and humidity range between -40°C to +65°C (-40°F to +150°F). The built-in memory contains all calibration and configuration information. Therefore the sensor ships pre calibrated and are ready for immediate operation. An intelligent sensor self-test function allows for predictive maintenance. The intrinsically safe connection of the sensor eliminates the need for a flame arrestor, giving you faster response times and higher sensitivity.

---

### Easy device management via digital communication

The Dräger Polytron 8100 is equipped with digital interfaces allowing for quick and easy remote interrogation of the transmitter's state. Integration with existing asset management systems such as PACTware™ is possible via DTM.

In addition to the common HART® communication system, the fieldbus interfaces with PROFIBUS® PA, FOUNDATION fieldbus™ H1, and Modbus RTU are also available.

---

### Same design, same operating principle

The Dräger Polytron 8100 belongs to the Polytron 8000 series. All transmitters in this series have the same design and user interface. This allows for uniform operation with reduced training and maintenance requirements.

The large graphic backlit display shows status information clearly and in an easy to use format. The measured gas concentration, selected gas type, and measuring unit are displayed during normal operation. Colored LEDs (green, yellow and red) provide additional alarm and status information.

The Polytron 8100 is operated by means of a magnetic wand over contact surfaces.

---

### Three relays for controlling external equipment

Upon request, the Dräger Polytron 8100 can also be supplied with three integrated relays. This enables you to use it as an independent gas detection system with two arbitrarily adjustable concentration alarms and one fault alarm. Audio alarms, signal lights, or similar devices can thus be controlled locally without an additional cable between the transmitter and central controller.

---

### Safe, robust housing for every application

Polytron 8100 features a Class I, Div. 1 rated explosion proof enclosure made from aluminum or stainless steel, making it suitable for a wide range of environmental conditions. A protection type "e" version includes a

## Benefits

convenient docking station which allows installation in hazardous atmospheres without running conduit (where approved).

---

### Remote sensor option does not require conduit

The optional remote sensor enclosure enables the sensor to be installed away from the transmitter. This makes it easy to place the sensor close to a potential gas cloud in an inaccessible location while keeping the display at eye level. Because the sensor is connected to the transmitter through an intrinsically safe port, this eliminates the need to run conduit for mounting a remote sensor. And to make things even easier, Dräger includes cabling up to 100 feet (30 meters) long. The intrinsically safe connection also allows 'hot swaps' of the sensor in a hazardous atmosphere without removing power or declassifying the area.

---

### More functions through dongles

With different software dongles, additional functions can be added to the Polytron 8100. The data logger dongle comes standard and continuously records gas readings and events. A sensor test dongle is available for additional sensor self-test functionality. A third dongle is available for advanced sensor diagnosis. These dongles indicate the sensor's vitality, giving you an estimate of the sensor's remaining service life.

## System Components



D-27771-2009

---

### Dräger REGARD® 3900

The Dräger REGARD® 3900 is a standalone, self contained control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable between 1 and 16 channels, depending upon the type and quantity of input/output boards installed.

## System Components



ST-335-2004

### Dräger REGARD®-1

The Dräger REGARD®-1 is a standalone, self contained single channel control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable for a single input from either a 4 to 20 mA transmitter or a Dräger Polytron® SE Ex measuring head.

## Accessories



D-15035-2010

### Docking station

The docking station is included with all transmitters in the Polytron® 5000 and Polytron® 8000 series for protection type "e", increased safety. This also facilitates pre-assembly.



D-86389-2013

### Splash guard

The Splash guard protects the sensor against splash water and dirt.

## Accessories



D-85345-2.013

---

### Duct mount kit

The duct mount kit enables gas monitoring inside ventilation ducts while keeping the transmitter outside.

## Technical Data

### Dräger Polytron® 8100 EC

Type	Explosion proof / flameproof enclosed transmitter ("d") or combined with increased safety ("d/e")			
Gases	Toxic gases and oxygen, dependent on the sensor used			
Measuring ranges	Customized adjustment, see sensor data sheet			
Display	Backlit graphic LCD; 3 Status LEDs (green/yellow/red)			
Electrical data	Signal output analog	Normal operation	4 to 20 mA	
		Maintenance	Constant 3.4 mA or 4 mA ±1 mA 1 Hz modulation; (adjustable)	
		Fault	< 1.2 mA	
	Signal output digital	HART®, PROFIBUS® PA, FOUNDATION fieldbus™ H1 and Modbus RTU		
	Power supply	10 to 30 V DC, 3-wire		
	Power consumption	w/o relay, non-remote	80 mA at 24 V	
w/ relay, remote		100 mA at 24 V		
Relay specification (option)	2 alarm relays and 1 fault relay, SPDT 5 A @ 230 VAC, 5 A @ 30 VDC, resistance-bound			
Environmental conditions (see sensor data sheet)	Temperature	-40 to 65°C (-40 to 149°F) without relay -40 to 65°C (-40 to 149°F) with relay		
	Pressure	20.7 to 38.4 inch Hg / 700 to 1,300 mbar		
	Humidity	0 to 100% r. h., non-condensing		
Housing	Transmitter housing	Epoxy coated copper-free aluminum or stainless steel SS316 L		
	Sensor housing	Polyamide		
	Enclosure protection type	NEMA 4X & 7, IP65/66/67		
	Cable entry point	3/4" NPT threaded holes or M20 cable gland		
	Dimensions (H x W x D), approx.	w/o docking station	11.0" x 5.9" x 5.1" / 280 x 150 x 130 mm	
		w/ docking station	11.0" x 7.1" x 7.5" / 280 x 180 x 190 mm	
	Weight, approx.	w/o docking station Aluminum	6.6 lbs / 3.0 kg	
w/o docking station SS316 L		11.0 lbs / 5.0 kg		
w/ docking station Aluminum		10.0 lbs / 4.5 kg		
w/ docking station SS316 L		14,3 lbs / 6.5 kg		

### Approvals\*

UL	Class I, Div 1, Groups A, B, C, D; Class II, Div 1, Groups E, F, G; Class I, Zone 1, Group IIC; T-Code T6/T4	
CSA	Class I, Div 1, Groups A, B, C, D; Class II, Div 1, Groups E, F, G; Class I, Zone 1, Group IIC; T-Code T6/T4	
IECEX	4-20-mA HART®	Ex db [ia] IIC T6/T4 Gb, -40 ≤ Ta ≤ +40/+70°C; "d" version Ex db e [ia] IIC T6/T4 Gb, -40 ≤ Ta ≤ +40/+70°C; "e" version; Ex tb [ia] IIIC T135°C Db
	PROFIBUS® & FF	Ex db ia [ia] IIC T6/T4 Gb, -40 ≤ Ta ≤ +40/+70°C; "d" version Ex db e ia [ia] IIC T6/T4 Gb, -40 ≤ Ta ≤ +40/+70°C; "e" version;

## Technical Data

ATEX	4-20-mA HART®	Ex tb [ia] IIIC T135°C Db II 2G Ex db [ia] IIC T6/T4 Gb, -40 ≤ Ta ≤ +40/+70°C; "d" version II 2G Ex db e [ia] IIC T6/T4 Gb, -40 ≤ Ta ≤ +40/+70°C; "e" version II 2D Ex tb [ia] IIIC T135°C Db
	PROFIBUS® & FF	II 2G Ex db ia [ia] IIC T6/T4 Gb, -40 ≤ Ta ≤ +40/+70°C; "d" version II 2G Ex db e ia [ia] IIC T6/T4 Gb, -40 ≤ Ta ≤ +40/+70°C; "e" version II 2D Ex tb [ia] IIIC T135°C Db
CE markings		ATEX (Directive 2014/34/EU) Electromagnetic Compatibility (Directive 2014/30/EU) Low Voltage (Directive 2014/35/EU)
Shipping approvals (for oxygen sensors only)		DNV GL, ABS
MED approval B (for oxygen sensors only)		Certificate no. 61549/ 50 – 13 HH
MED approval D (for oxygen sensors only)		Certificate no. 12031 – 10 HH
Performance approval (for oxygen sensors only)		Certificate no. BVS 13 ATEX G 001 X PFG 14 G 001X
SIL 2 certified by TUEV Sued		Certificate no. Z10 1207 53474 013
* All docking station versions are only ATEX/IECEx approved		

## Ordering Information

### Dräger Polytron® 8100 EC

Dräger Polytron® 8100 EC d A 4-20/HART®	83 44 403
Dräger Polytron® 8100 EC d A 4-20/HART® relay	83 44 404
Dräger Polytron® 8100 EC e A 4-20/HART® (incl. Docking Station)	83 44 421
Dräger Polytron® 8100 EC e A 4-20/HART® relay (incl. Docking Station)	83 44 422
Dräger Polytron® 8x0 Kit (Custom configuration e. g. stainless steel housing)	83 44 800

### Accessories

Magnetic wand	45 44 101
Sensor Test Dongle	83 17 619
Diagnostic Dongle	83 17 860
Pipe mount bracket	45 44 198
Duct mount kit	68 12 725
Duct mount adapter for remote EC sensing head	83 17 617
Remote adapter RS stainless steel	83 23 404
EC Sensing Head Remote w/ mount kit	68 12 684
IR Connection Kit Polytron® 5000/8000	45 44 197
PolySoft	83 23 405
PolySoft premium	83 23 411
Connection cable w/ plug for Remote EC	16 ft / 5 m 83 23 305
Sensing Head	49 ft / 15 m 83 23 315
	98 ft / 30 m 83 23 330

## Ordering Information

Splash guard		68 12 510
Gassing adapter	PE incl. tubing	45 09 314
Calibration adapter Viton®		68 10 536

HART® is a registered trademark of the HART Communication Foundation.

FOUNDATION fieldbus™ is a registered trademark of the Fieldbus Foundation™.

PROFIBUS® is a registered trademark of PROFIBUS and PROFINET International (PI).

PACTware™ is a registered trademark of Pepperl+Fuchs GmbH.

Viton® is a registered trademark of the DuPont company.

### CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA  
Moislinger Allee 53–55  
23558 Lübeck, Germany  
[www.draeger.com](http://www.draeger.com)

### SYSTEM CENTERS

**P. R. CHINA**  
Dräger Safety Equipment  
Co., Ltd.  
A22 Yu An Rd, B Area,  
Tianzhu Airport Industrial Zone,  
Shunyi District, Beijing 101300  
Tel +86 10 80 49 80 00  
Fax +86 10 80 49 80 05

### GERMANY

Dräger Safety AG & Co. KGaA  
Revalstrasse 1, 23560 Lübeck  
Tel +49 451 882-2794  
Fax +49 451 882-4991

### UNITED KINGDOM

Dräger Safety UK Ltd.  
Blyth Riverside Business Park  
Blyth, Northumberland NE24 4RG  
Tel +44 1670 352 891  
Fax +44 1670 544 475

### REGION EUROPE

Dräger Safety AG & Co. KGaA  
Revalstraße 1  
23560 Lübeck, Germany  
Tel +49 451 882 0  
Fax +49 451 882 2080  
[info@draeger.com](mailto:info@draeger.com)

### USA

Dräger, Inc., 3135 Quarry Road  
Telford, PA 18969  
Tel +1 800 4DRAGER  
(+1 800 437 2437)  
Fax +1 215 723 5935  
[info.usa@draeger.com](mailto:info.usa@draeger.com)

### REGION ASIA PACIFIC

Dräger Safety Asia Pte Ltd  
25 International Business Park  
#04-20/21 German Centre  
Singapore 609916  
Tel +65 6308 9400  
Fax +65 6308 9401  
[asia.pacific@draeger.com](mailto:asia.pacific@draeger.com)

### REGION CENTRAL AND SOUTH AMERICA

Dräger Panama Comercial  
S. de R.L.  
Complejo Business Park  
V tower, 10th floor, Panama City  
Tel +507 377-9100 / Fax: -9130  
[contactcsa@draeger.com](mailto:contactcsa@draeger.com)

### REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA  
Branch Office  
P.O. Box 505108  
Dubai, United Arab Emirates  
Tel +971 4 4294 600  
Fax +971 4 4294 699  
[contactuae@draeger.com](mailto:contactuae@draeger.com)

Locate your Regional  
Sales Representative at:  
[www.draeger.com/contact](http://www.draeger.com/contact)

